

BULLETIN!

TWIST FIX BRACKETS

NO NUTS!

TWIST FIX BRACKETS!

TWIST FIX BRACKETS ARE SUPPLIED WITH EVERY SIZE DOOR BUT ARE NOT REQUIRED ON DOORS UP TO 2743MM (9'0") WIDE AND 2250MM (7'4") HIGH AND UNDER 70KG.

When will I use twist fix brackets?

Doors up to 2743mm (9'0") wide and 2250mm (7'4") high and under 70kg don't require twist fix brackets. You just fix straight through the frame fixing points for a secure and solid frame installation.

Doors over this size do require twist fix brackets, they add extra rigidity.

Although not required on some doors, all fixing packs include them to assist with installation. They can be used outbound of the frame to locate a secure fixing when inbound fixing is not possible or sufficiently solid.



Why twist fix?

Simple – they just locate through the frame and twist into position ready for fixing through. No fiddly nut and bolt to secure each bracket, just a super quick twist, fix and done!

		Width																		
Height	2084	2134	2235	2286	2388	2438	2591	2743	3048	3353	3658	3962	4216	4267	4420	4572	4877	5182	5500	Height
3000																				3000
2875																				2875
2750																				2750
2625																				2625
2500																				2500
2375																				2375
2250																				2250
2204																				2204
2175																				2175
2125																				2125
2084																				2084
2050																				2050
2000																				2000
1925																				1925
1875																				1875
Height	2084	2134	2235	2286	2388	2438	2591	2743	3048	3353	3658	3962	4216	4267	4420	4572	4877	5182	5500	Height
		Width																		

Requires frame leg holes (standard frame) and twist fix frame leg brackets.

Twist fix frame leg brackets not required, but provided to assist with installation*.

No holes in frame leg as an option (between fix frame with stiffener brackets required).

Twist fix frame leg brackets required.

No holes in frame leg as an option (between fix frame with stiffener brackets required).

*Doors below 70kg do not require twist fix brackets for strengthening, however they are included with all doors to assist with installation. They can be used outbound of the frame to locate a secure fixing when inbound fixing is not possible or sufficiently solid.

All doors (back fix and between fix) will include one of the following fixing kits:

Back fix kit 1

- 4 x horizontal track hangers
- 2 x spacer bar side mounting rails
- 8 x Twist fix retaining brackets (vertical tracks)

Back fix Kit 2

- 4 x horizontal track hangers
- 2 x spacer bar side mounting rails
- 10 x Twist fix retaining brackets (vertical tracks)

Back fix kit 3

- 6 x horizontal track hangers
- 2 x rear mounting rails
- 12 x Twist fix retaining brackets (vertical tracks)

Want to know more? Call the team on: 01925 924 050