

ROBUST, SIMPLE, COST-SAVING!

NEW

Teckentrup Roller Shutter System "easy"

THE NEW AND INNOVATIVE ROLLER SHUTTER DESIGN FOR STANDARD APPLICATIONS

**Huge savings by reducing the installation time by approx. 40%!
Can be installed by just 1 person!**

- Easy and trouble-free installation!**
- Compact design
 - Save up to 40% installation time
 - Space-saving console for all door sizes
 - Consoles connected to guide rails – no time-consuming measuring and marking required (Teckentrup property rights)
 - Winding shaft position determined automatically
 - High-strength connection system between the shutter curtain and the shaft (Teckentrup property rights)
 - Guide rail system – suitable for all shutter types and sizes
 - Reliable brand-name drive with pre-wired deadman or pulse control unit

Now available with pulse control unit!

3 versions available



Roller shutter profile ThermoTeck "easy"



Roller shutter profile 6010 visio "easy"



Roller grille TG-X "easy"

WE OPEN THE DOORS FOR PROGRESS



Innovative Details – Increased Efficiency

IMPRESSIVE TECHNOLOGY MAKES IT POSSIBLE

Simple, practical and safe

The new Teckentrup roller shutter system “easy” is characterized by its simple and robust design. Individual components have been intelligently designed and perfectly harmonized to deliver real added value. Time-consuming measuring tasks, e.g. for attaching the console and determining the winding shaft position, are a thing of the past. Furthermore, installation is facilitated by the pre-wired control unit and drive. The required installation time can be reduced by up to 40% in comparison to conventional roller shutter systems.



The pre-wired control unit is integrated in the reliable brand-name drive. Comfortable shutter control occurs via a plug-in, pre-wired button with 3 options (open-stop-close).



Durable and high-strength connection system between the shutter curtain and the shaft (Teckentrup property rights). The octagonal winding shaft, incl. shaft journal, is fully galvanized.



The roller shutter curtain is pre-assembled on the winding shaft and can be simply fitted into the console. The space-saving console is bolted to the runner rail – no time-consuming measuring and marking required.



Pre-punched runner rails facilitate installation. The floor seal is integrated in the bottom profile and ensures a harmonious appearance inside and outside.



Internet: www.teckentrup.biz