Order form - Insulated Side Hinged Garage Door GSW 40-L



Date:		Customer Order Number:				Number of Sheets:			
Customer Name:			Contact Number:						
Deliver To:			JL Delivery R				Required Week Con	nmencing:	
<u> </u>									
Opening	Double RIGHT Leading Open OUT Open	e LEFT Dou ng Lea OUT Ope	en IN* Coper	n IN*	H C	ingle EIGHT linged Ipen OUT Den-in doo	LEFT Hinged Open OUT	Single Single RIGHT Hinged Open IN Open IN	
NOTE: Order by over frame dimensions. To calculate the over frame size, deduct 20mm from the width and 10mm from the height of the structural opening size to allow for coursing tolerance.									
Over Frame Width: Quantity:									
	Door Style: Standard:	or Style: Standard: Traditional:		Toplight:				Costal paint upgrade	
Panel, Frame & Hinges	Panel Surface: Wood(rain Stucco Smooth			Micro-Profile	ed		(frame and external face of panels)	
	Panel Colour: (RAL 9002 Inside) RAL 9	9016 Trend/+ Colour:			RAL Colour:				
	Wood Design: (RAL 9002 Inside) Golde	n Oak Rosewood Night Oak			Winchester				
	Frame Colour: Trend	+ Colour:			RAL Colour:				
	Hinges: Concealed hinges are standard. Surface mounted hinges are available as an option: Surface mounted hinges (colour options below)								
	Complete Surface Mounted Hinge Colour: Trend/+ Colour: RAL Colour:								
	Half & Half Surface Mounted Hinge Colour: (Example, white frame & black door leaf - Hinges will be half white and half black to match frame and panel colour.)								
Orientation	Panel orientation for Georgian, Standar Centre Rib, Solid or Traditional Style:	d Rib, Horizon	ntal Verl	tical	1111	Leaf s	plit: 1/2 - 1	/2 Asymmetric	
	Type Rectangle 1 610 x 270 Type Aluminium Al				Reling Glazing Quantity: Day 280 x 280 Please describe the position of the windows and/				
	Type Cross Mullion 1 610 x 270			or decals required. Eg, top panel evenly spread or vertically aligned on the left or vertically aligned					
Polymer Glazing		ype Rhombus 1 610 x 270 Type Aluminium			Ø 280	on	the right.		
		Type Aluminium Gamma 534 x 344							
	Type Rectangular 3 980 X 140 = Type Square 1 Polymer 270 x 270		Type Aluminium Kappa 1860 x 180						
	Type Square 2 Polymer 270 x 270		Type Aluminium Athena 406 x 203						
Pol	· · · · · · · · · · · · · · · · · · ·	680 x 370	Type Aluminium Versus			-			
	Leading Colour: GSA Aluminium Window Sec	etion	Glazing Polymer: Clear Satin			<u> </u>			
	Style: Leading Co	•		Aluminium Strip Threshold Profile (4mm) (in place of standard lipped 3-part threshold) 1-Part Aluminium Raised Threshold (in place of standard lipped 3-part threshold)					
1	lazing Polymer: Clear	Frosted Satin	Window Orientation:		Four-Sided Frame 55mm Threshold (in place of standard lipped 3-part threshold)				
F	rame Colour: Trend/+:		Horizontal Vertical		Four-Sided Frame 40mm Full Overlap Threshold (in place of standard lipped 3-part threshold) 2-Part Strip Threshold (centre & back part in place of standard lipped 3-part threshold)				
	RAL:		vei ticai			Black Powder Coated Lever Handle (Supplied in place of Stainless Steel) Lever Handle Upgrade 316 Stainless Steel*			
Decals	Type Access 1 431 x 40 Type Access 2 430 x 40			Options	3-Point Pin Locking with Standard Stainless Steel Lever Handle (Active leaf) 3-Point Hook Locking with CarTeck Lever Handle* (Active leaf)				
	Type Access 2 430 x 40 Type Access 3 215 x 40			Se Se	Handle Finish (Sa	atin Nickel as Standard):			
	Type Access 4 400 x 86	——— Pequired:		Accessories	*Recommended for high salinity environments. Stainless D Handle Ø 38 x 1200mm Qty: Stainless D Handle Ø 38 x 1500mm Qty: D Handle 3-Point Locking				
	Type Access 5 180 x 18	30 <u> </u>	Notes						
	Type Access 6 70 x 70	Note			Drip Guard (Recommended on inward opening doors) Foot Stops (Supplied in place of door stays) Additional Keys Qty: Finger Pull				
	Type Access 7 150 x 15	50 🖳							
	Type Access 8 194 x 19 Type Access 9 436 x 40				Letter Box Spy Hole	Code Lock Smart Lock		Smart Upgrade Pet Flap Fitting	
	Type Access 9 436 x 40 Type Access 10 431 x 13	101/	TOTAL £		SEND FORM		AVE FORM	RESET FORM	