

# E 60/120/240-1 „Teckentrup HC” - BS

Fire resistant single leaf steel doorsets

Optional glazing

Optional over and sidepanels



## Text example

Compile and tender according to requirements.  
Please refer to Technical Data below for respective details.  
Updated 1<sup>st</sup> June 2015

Position	No. of pieces	Item	Unit price €	Total price €
		60/120/240 minute fire rated steel doorset tested to the European fire test standard, BS EN 1634-1. Type of handing DIN left/right. Flush door leaf hung from 1½ pairs of 3. 4 mm thick, grade 316 steel hinges. Galvanised and prime coated similar to RAL 9002 (grey white), 45 mm thick. Galvanised and prime coated 1.5 mm thick steel door frame, double rebate profile. Mortice lock with stainless steel levers and overhead door closer.		



## Technical data

also available in **stainless steel**

- upon request -

### WCL Certifire certification:

Certificate No: CF 673  
Fire Tested to BS EN 1634-1 up to 240 minutes integrity

### Installation in:

- Masonry
- Concrete
- Autoclaved aerated concrete
- Partition systems

### Approved dimensions:

Structural opening width: 625 – 1391 mm  
Structural opening height: up to 3070 mm  
Subject to max. Leaf area 3,96m<sup>2</sup>

### Door leaf:

Double-skinned  
Door leaf thickness: 45 mm  
Sheet thickness: 1,0 mm \ 1,5 mm

### Frame:

Double rebate frame 1.5 mm thick  
Silicone compression seal

### Surface:

Door leaf/Frame galvanized and prime coated, similar to RAL 9002 (grey white).

### Fittings:

- 3 - 5 galvanized steel hinges
- 1 overhead door closer
- Mortice lock with stainless steel levers, escutcheon, prepared for profile cylinder
- Stainless steel handle set

### Glazing:

- 6 mm thick clear "Pyran S" (up to 2 hours)

### Optional equipment:

- Dog bolt hinges
- Diverse lock and handle options
- Stainless steel pull handle
- Stainless steel push plate
- Stainless steel kick plate
- Overhead door closer in accordance with EN 1154
- Deadlock
- Friction Stay
- Viewer
- Magnetic Lock
- Extruded aluminium threshold c/w seal prep. for internal metal conduits
- hole for magnetic contact
- Panic escape devices
- Louvre Systems

# E 60/120/240-1 „Teckentrup HC” - BS

Fire resistant single leaf steel doorsets  
 Optional glazing  
 Optional over and sidepanels

