

E 60/120/240-2 „Teckentrup HC” - BS

Fire resistant double leaf steel doorsets

Optional glazing

Optional over and sidepanels



Text example

Compile and tender according to requirements.
Please refer to technical data below for respective details.
Updated 1st June 2015

Position	No. of pieces	Item	Unit price €	Total price €
		60/120/240 minute fire rated steel doorset tested to the European fire test standard, BS EN 1634-1. Type of handing DIN left/right. Flush door leaf hung from 1½ pairs of 3. 4 mm thick, grade 316 steel hinges. Galvanized and prime coated similar to RAL 9002 (Grey white), 45 mm thick. Galvanized and prime coated 1.5 mm thick steel door frame, double rebate profile. Mortice lock with stainless steel levers and 2 overhead door closer.		

also available in stainless steel

- upon request -



Technical data

WCL Certifire certification:

Certificate No: CF 673
Fire Tested to BS EN 1634-1 up to 240 minutes integrity

Installation in:

- Masonry
- Concrete
- Autoclaved aerated concrete
- Partition systems

Approved dimensions:

Structural opening width: 1400 – 2800 mm
Structural opening height: up to 3070 mm
Subject to max. Leaf area 3.96m²

Door leaf:

Double-skinned
Door leaf thickness: 45 mm
Sheet thickness: 1.0 mm \ 1.5 mm

Frame:

Double rebate frame 1.5 mm thick
Silicone compression seal

Surface:

Door leaf/Frame galvanized and prime coated, similar to RAL 9002 (Grey white).

Fittings:

- 6 - 10 stainless steel hinges
- 2 overhead door closer
- Mortice lock with stainless steel levers, escutcheon, prepared for profile cylinder
- Stainless steel handle set

Glazing:

- 6 mm thick clear “Pyran S” (up to 2 hours)

Optional equipment:

- Dog bolt hinges
- Diverse lock and handle options
- Stainless steel pull handle
- Stainless steel push plate
- Stainless steel kick plate
- Overhead door closer in accordance with EN 1154
- Mortice deadlock
- Friction Stay
- Door Leaf Selector
- Viewer
- Magnetic Lock
- Extruded aluminium threshold c/w seal prep. for internal metal conduits
- hole for magnetic contact
- Panic escape devices
- Louvre Systems

E 60/120/240-2 „Teckentrup HC” - BS

Fire resistant double leaf steel doorsets

Optional glazing

Optional over and sidepanels

